

**PENTAX** | R-1500N Series

# Total Surveying Solution

- Long EDM range measuring distance in reflectorless up to 500m and in prism mode up to 3,000m
- Large internal memory: 60000 points.
- Dual display as a standard equipment
- Easy transfer to a PC via SD card, USB mini and RS-232C data port
- Pre-loaded versatile software functions
- Dual battery system for long time use



**INCREASE YOUR  
WORK EFFICIENCY**

**FASTER  
TURNAROUND**



Model	R-1502N		R-1505N
<b>Telescope</b>	Image	Erect	
	Magnification	30 x	
	Effective Aperture	45mm	
	Resolving Power	3.0"	
	Field of View	1°20'	
	Minimum Focus	1.0m	
	Focus	Manual	
	Laser Class	Visible Laser: Class IIIa (Reflectorless, sheet) / Class I (Prism)	
<b>Measurement Range (Good condition) *3</b>			
	Reflectorless *1	1.5 ~ 500m	
	Reflector Sheet *2	1.5 ~ 800m	
	Mini Prism	1.5 ~ 800m	
	1P	1.5 ~ 3000m	
	3P	1.5 ~ 9999m	
<b>Accuracy</b>	Prism	±(2+2ppm x D)mm	
	Reflector Sheet	±(3+2ppm x D)mm	
	Reflectorless	2.0m ~ 150m: ±(3+2ppm x D)mm	
		150m ~ 300m: ±(5+2ppm x D)mm	
		300m ~ 500m: ±(10+2ppm x D)mm	
Minimum Count	0.1mm (Fine mode), 1mm (Normal mode), 10mm (Track mode)		
<b>Measurement Time *4</b>	Repeat Meas.	Fine (0.1mm)	Prism / Ref.sheet 3.0sec., Ref.less 3.0sec. (over 300m 5.0sec.)
		Normal (1mm)	Prism / Ref.sheet 2.0sec., Ref.less 2.0sec. (over 300m 4.0sec.)
		Track (10mm)	Prism / Ref.sheet 0.4sec., Ref.less 0.4sec. (over 300m 0.4sec.)
	Initial Meas.	Fine (0.1mm)	1.5 ~ 300m 3.5sec., over 300m ~ 13sec.
		Normal (1mm)	1.5 ~ 300m 2.4sec., over 300m ~ 12sec.
		Track (10mm)	1.5 ~ 300m 2.5sec., over 300m ~ 12sec.
<b>Angle Measurement</b>	Measuring Method	Absolute rotary encoder	
	Detection Method	Vertical / Horizontal angle	
		2 sides	
	Minimum Count	1" / 5"	
Accuracy (ISO17123-3)	2"		5"
<b>Compensator</b>	Axis	2 axis	
	Range	±3'	
<b>Tangent Screw</b>	1 Seed/Clamping (<30")		
<b>Sensitivity of Vials</b>	Plate Level	30"/1div. (electrical)	
	Circular Level	30"/2mm	
<b>Plummet</b>	Visible Laser, ±0.5mm (instrument height 1.5m)		
<b>Base</b>	Detachable		
<b>Dust and Water Protection</b>	IP55 (instrument only)		
<b>Ambient Temperature</b>	-20°C ~ 50°C / -4°F ~ 122°F (Working range)		
<b>Tripod Thread</b>	5/8" x 11		
<b>Dimensions/Weight</b>	Dimensions	183 (W) x 342(H) x 167(L)mm	
	Weight (incl. Battery)	5.4 kg	
<b>Carrying Case</b>	440(W) x 370 (H) x 275 (L)mm /3.9 kg		
<b>Battery Pack</b>	Power Source	Li-ion 2,500mAh X 2 = 5,000mAh (hotswap)	
	Operation Time	Continuous approx. 9.0 hrs (ETH+EDM) with approx. 2.5hrs. of charging time	
	Weight	5400g	
<b>Battery Charger and AC Adapter</b>			
	Input Voltage (AC05)	AC 100 ~ 240V	
	Output Voltage (BC05)	DC8.4V	
<b>Data Process</b>	Data Recording Method	Internal Memory	
	Memory Capacity	Over 2GB	
	Coordinates Data	60000	
	Special Function	PowerTopoExpress 2	
	I/F	RS-232C, SD CARD, USB mini, Bluetooth (class2)	
<b>Display / Keyboard</b>	Display Type	Graphic LCD / 20 characters x 8 lines / 240 x 96 pixels	
	Quantity	2	
	Keys	22 each (12 numeric / 5 function / 5 special)	
<b>Display Back Light</b>	Intensity settings: 10 steps		
<b>Laser Pointer</b>	Yes		
<b>Date Clock</b>	Yes		

\* Specifications are subject to change without notice

\*1 The measurement range and accuracy of reflectorless, and time required to measure may vary by the shape, size of surface area and reflection rate of the target and its environment.

The measurement range of reflectorless is determined by the white side of the Kodak Gray Card.

\*2 Reflector sheet: Genuine Reflector sheet

\*3 The measurement range may vary by conditions of the environment.

Normal conditions: 20km visibility with slight shimmer

Good conditions: 40km visibility with overcast, no heat, no shimmer and moderate wind.

\*4 EDM measuring time is determined in good conditions. It may take longer than usual to measure the distance exceeding 4000m in prism mode and 300m in reflectorless mode.

**TI Asahi Co., Ltd.**

**International Sales Department**

4-3-4 Ueno Iwatsuki-Ku, Saitama-Shi

Saitama, 339-0073 Japan

Tel.: +81-48-793-0118

Fax: +81-48-793-0128

E-mail: international@tiasahi.com

[www.pentaxsurveying.com/en/](http://www.pentaxsurveying.com/en/)

Your Official Pentax Dealer



The CE marking assures that this product complies with the requirements of the EC directive for safety.

**JSIMA**  
Japan Surveying Instruments Manufacturers' Association

Member symbol of the Japan Surveying Instruments Manufacturers' Association representing the high quality surveying products.

